



## LM2937 500-mA Low Dropout Regulator

### 1 Features

- Fully Specified for Operation Over  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$
- Output Current in Excess of 500 mA
- Output Trimmed for 5% Tolerance Under all Operating Conditions
- Typical Dropout Voltage of 0.5 V at Full Rated Load Current
- Wide Output Capacitor ESR Range, up to  $3\ \Omega$
- Internal Short Circuit and Thermal Overload Protection
- Reverse Battery Protection
- 60-V Input Transient Protection
- Mirror Image Insertion Protection

### 2 Applications

- Automotive
- Industrial Control
- Point-of-Load regulation


### 3 Description

The LM2937 is a positive voltage regulator capable of supplying up to 500 mA of load current. The use of a PNP power transistor provides a low dropout voltage characteristic. With a load current of 500 mA the minimum input to output voltage differential required for the output to remain in regulation is typically 0.5 V (1-V ensured maximum over the full operating temperature range). Special circuitry has been incorporated to minimize the quiescent current to typically only 10 mA with a full 500-mA load current when the input to output voltage differential is greater than 3 V.

The LM2937 requires an output bypass capacitor for stability. As with most low dropout regulators, the ESR of this capacitor remains a critical design parameter, but the LM2937 includes special compensation circuitry that relaxes ESR requirements. The device is stable for all ESR below  $3\ \Omega$ . This allows the use of low ESR chip capacitors.

Ideally suited for automotive applications, the LM2937 will protect itself and any load circuitry from reverse battery connections, two-battery jumps, and up to 60-V/–50-V load dump transients. Familiar regulator features such as short circuit and thermal shutdown protection are also built in.

**Simplified Schematic**



**Device Information<sup>(1)</sup>**

| PART NUMBER | PACKAGE    | BODY SIZE (NOM)      |
|-------------|------------|----------------------|
| LM2937      | TO-220 (3) | 14.986 mm x 10.66 mm |
|             | SOT (4)    | 6.50 mm x 3.5 mm     |
|             | TO-263 (3) | 10.18 mm x 8.41 mm   |

(1) For all available packages, see the orderable addendum at the end of the datasheet.



## Table of Contents




|                                                 |           |                                                                  |           |
|-------------------------------------------------|-----------|------------------------------------------------------------------|-----------|
| <b>1 Features</b> .....                         | <b>1</b>  | 7.1 Overview .....                                               | 11        |
| <b>2 Applications</b> .....                     | <b>1</b>  | 7.2 Functional Block Diagram .....                               | 11        |
| <b>3 Description</b> .....                      | <b>1</b>  | 7.3 Feature Description .....                                    | 11        |
| <b>4 Revision History</b> .....                 | <b>2</b>  | 7.4 Device Functional Modes .....                                | 12        |
| <b>5 Pin Configuration and Functions</b> .....  | <b>3</b>  | <b>8 Application and Implementation</b> .....                    | <b>13</b> |
| <b>6 Specifications</b> .....                   | <b>4</b>  | 8.1 Application Information .....                                | 13        |
| 6.1 Absolute Maximum Ratings .....              | 4         | 8.2 Typical Application .....                                    | 13        |
| 6.2 Handling Ratings .....                      | 4         | <b>9 Power Supply Recommendations</b> .....                      | <b>17</b> |
| 6.3 Recommended Operating Conditions .....      | 4         | <b>10 Layout</b> .....                                           | <b>18</b> |
| 6.4 Thermal Information .....                   | 4         | 10.1 Layout Guidelines .....                                     | 18        |
| 6.5 Electrical Characteristics: LM2937-5 .....  | 5         | 10.2 Layout Example .....                                        | 18        |
| 6.6 Electrical Characteristics: LM2937-8 .....  | 5         | <b>11 Device and Documentation Support</b> .....                 | <b>19</b> |
| 6.7 Electrical Characteristics: LM2937-10 ..... | 5         | 11.1 Trademarks .....                                            | 19        |
| 6.8 Electrical Characteristics: LM2937-12 ..... | 7         | 11.2 Electrostatic Discharge Caution .....                       | 19        |
| 6.9 Electrical Characteristics: LM2937-15 ..... | 7         | 11.3 Glossary .....                                              | 19        |
| 6.10 Typical Characteristics .....              | 8         | <b>12 Mechanical, Packaging, and Orderable Information</b> ..... | <b>19</b> |
| <b>7 Detailed Description</b> .....             | <b>11</b> |                                                                  |           |

## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| Changes from Revision E (June 2013) to Revision F                                                                                                                                                                                                                                                                    | Page |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| <ul style="list-style-type: none"> <li>Changed format to meet new TI standards; added Device Information and Handling Ratings tables; updated connection drawings; rename Functional Description and Applications sections, reformat and add new information, add Devices and Documentation section .....</li> </ul> | 1    |

## 5 Pin Configuration and Functions



### Pin Functions

| NAME   | PIN |     |     | I/O | DESCRIPTION                                                                                                                                                                                                                                                                    |
|--------|-----|-----|-----|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | NDE | KTT | DCY |     |                                                                                                                                                                                                                                                                                |
| INPUT  | 1   | 1   | 1   | I   | Unregulated voltage input                                                                                                                                                                                                                                                      |
| GND    | 2   | 2   | 2   | —   | Ground                                                                                                                                                                                                                                                                         |
| OUTPUT | 3   | 3   | 3   | O   | Regulated voltage output. This pin requires an output capacitor to maintain stability. See the <a href="#">Detailed Design Procedure</a> section for output capacitor details.                                                                                                 |
| GND    | TAB | TAB | 4   | —   | Thermal and ground connection. Connect the TAB to a large copper area to remove heat from the device. The TAB is internally connected to device pin 2 (GND). Connect the TAB to GND or leave floating. Do not connect the TAB to any potential other than GND at device pin 2. |

## 6 Specifications

### 6.1 Absolute Maximum Ratings<sup>(1)(2)</sup>

over operating free-air temperature range (unless otherwise noted)

|                                           |                        | MIN                | MAX | UNIT |
|-------------------------------------------|------------------------|--------------------|-----|------|
| Input voltage (V <sub>IN</sub> )          | Continuous             |                    | 26  | V    |
|                                           | Transient (t ≤ 100 ms) |                    | 60  |      |
| Internal power dissipation <sup>(3)</sup> |                        | Internally limited |     |      |
| Maximum junction temperature              |                        |                    | 150 | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) If Military/Aerospace specified devices are required, please contact the Texas Instruments Sales Office/Distributors for availability and specifications.
- (3) The maximum allowable power dissipation at any ambient temperature is  $P_{MAX} = (125^{\circ}\text{C} - T_A)/R_{\theta JA}$ , where 125 is the maximum junction temperature for operation,  $T_A$  is the ambient temperature, and  $R_{\theta JA}$  is the junction-to-ambient thermal resistance. If this dissipation is exceeded, the die temperature will rise above 125°C and the electrical specifications do not apply. If the die temperature rises above 150°C, the LM2937 will go into thermal shutdown.

### 6.2 Handling Ratings

|                    |                           | MIN                                                                         | MAX | UNIT         |
|--------------------|---------------------------|-----------------------------------------------------------------------------|-----|--------------|
| T <sub>stg</sub>   | Storage temperature range | –65                                                                         | 150 | °C           |
| V <sub>(ESD)</sub> | Electrostatic discharge   | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins <sup>(1)</sup> |     | –2000 2000 V |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

### 6.3 Recommended Operating Conditions<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                                                       |                                | MIN                    | NOM | MAX | UNIT |
|-------------------------------------------------------|--------------------------------|------------------------|-----|-----|------|
| Junction temperature (T <sub>J</sub> ) <sup>(2)</sup> | LM2937ET (NDE), LM2937ES (KTT) | –40                    |     | 125 | °C   |
|                                                       | LM2937IMP (DCY)                | –40                    |     | 85  |      |
| Input voltage (V <sub>IN</sub> )                      |                                | V <sub>OUT</sub> + 1 V |     | 26  | V    |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The maximum allowable power dissipation at any ambient temperature is  $P_{MAX} = (125^{\circ}\text{C} - T_A)/R_{\theta JA}$ , where 125°C is the maximum junction temperature for operation,  $T_A$  is the ambient temperature, and  $R_{\theta JA}$  is the junction-to-ambient thermal resistance. If this dissipation is exceeded, the die temperature will rise above 125°C and the electrical specifications do not apply. If the die temperature rises above 150°C, the LM2937 will go into thermal shutdown.

### 6.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                              | LM2937             |        |        | UNIT |
|-------------------------------|----------------------------------------------|--------------------|--------|--------|------|
|                               |                                              | NDE <sup>(2)</sup> | KTT    | DCY    |      |
|                               |                                              | 3 PINS             | 3 PINS | 4 PINS |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 77.9               | 41.8   | 58.3   | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 35.5               | 43.5   | 39.2   |      |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 70.6               | 0.8    | N/A    |      |
| Ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 13                 | 23.5   | 7      |      |
| Ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 70.6               | 10.3   | 1.6    |      |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | 1                  | 22.5   | 22.5   |      |

- (1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).
- (2) Thermal information for the TO-220 package is for a free-standing package vertically mounted in the middle of a PCB which is compliant to the JEDEC HIGH-K 2s2p (JESD51-7) specifications. No additional heat sink is attached. See [Heatsinking TO-220 Package Parts](#) section for more information.

## 6.5 Electrical Characteristics: LM2937-5

Unless otherwise specified:  $V_{IN} = V_{OUT(NOM)} + 5\text{ V}$ ;  $I_{OUT(MAX)} = 500\text{ mA}$  for the TO-220 and DDPak/TO-263 packages;  $I_{OUT(MAX)} = 400\text{ mA}$  for the SOT-223 package; and  $C_{OUT} = 10\text{ }\mu\text{F}$ . Conditions and the associated minimum and maximum limits apply over the Recommended Operating temperature range for the specific package, unless otherwise noted.

| PARAMETER                         | CONDITIONS                                                                      | MIN  | TYP | MAX  | UNIT             |
|-----------------------------------|---------------------------------------------------------------------------------|------|-----|------|------------------|
| Output voltage                    | $T_A = T_J = 25^\circ\text{C}$ , $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$   | 4.85 | 5   | 5.15 | V                |
|                                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                    | 4.75 | 5   | 5.25 | V                |
| Line regulation                   | $(V_{OUT} + 2\text{ V}) \leq V_{IN} \leq 26\text{ V}$ , $I_{OUT} = 5\text{ mA}$ |      | 15  | 50   | mV               |
| Load regulation                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                    |      | 5   | 50   | mV               |
| Quiescent Current                 | $(V_{OUT} + 2\text{ V}) \leq V_{IN} \leq 26\text{ V}$ , $I_{OUT} = 5\text{ mA}$ |      | 2   | 10   | mA               |
|                                   | $V_{IN} = (V_{OUT} + 5\text{ V})$ , $I_{OUT} = I_{OUT(MAX)}$                    |      | 10  | 20   | mA               |
| Output noise voltage              | 10 Hz to 100 kHz, $I_{OUT} = 5\text{ mA}$                                       |      | 150 |      | $\mu\text{Vrms}$ |
| Long-term stability               | 1000 Hrs.                                                                       |      | 20  |      | mV               |
| Dropout voltage                   | $I_{OUT} = I_{OUT(MAX)}$                                                        |      | 0.5 | 1    | V                |
|                                   | $I_{OUT} = 50\text{ mA}$                                                        |      | 110 | 250  | mV               |
| Short-circuit current             |                                                                                 | 0.6  | 1   |      | A                |
| Peak line transient voltage       | $t_f < 100\text{ ms}$ , $R_L = 100\text{ }\Omega$                               | 60   | 75  |      | V                |
| Maximum operational input voltage |                                                                                 | 26   |     |      | V                |
| Reverse DC input voltage          | $V_{OUT} \geq -0.6\text{ V}$ , $R_L = 100\text{ }\Omega$                        | -15  | -30 |      | V                |
| Reverse transient input voltage   | $t_r < 1\text{ ms}$ , $R_L = 100\text{ }\Omega$                                 | -50  | -75 |      | V                |

## 6.6 Electrical Characteristics: LM2937-8

Unless otherwise specified:  $V_{IN} = V_{OUT(NOM)} + 5\text{ V}$ ;  $I_{OUT(MAX)} = 500\text{ mA}$  for the TO-220 and DDPak/TO-263 packages;  $I_{OUT(MAX)} = 400\text{ mA}$  for the SOT-223 package; and  $C_{OUT} = 10\text{ }\mu\text{F}$ . Conditions and the associated Minimum and Maximum limits apply over the Recommended Operating temperature range for the specific package, unless otherwise noted.

| PARAMETER                         | CONDITIONS                                                                      | MIN  | TYP | MAX  | UNIT             |
|-----------------------------------|---------------------------------------------------------------------------------|------|-----|------|------------------|
| Output voltage                    | $T_A = T_J = 25^\circ\text{C}$ , $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$   | 7.76 | 8   | 8.24 | V                |
|                                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                    | 7.6  | 8   | 8.4  | V                |
| Line regulation                   | $(V_{OUT} + 2\text{ V}) \leq V_{IN} \leq 26\text{ V}$ , $I_{OUT} = 5\text{ mA}$ |      | 24  | 80   | mV               |
| Load regulation                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                    |      | 8   | 80   | mV               |
| Quiescent Current                 | $(V_{OUT} + 2\text{ V}) \leq V_{IN} \leq 26\text{ V}$ , $I_{OUT} = 5\text{ mA}$ |      | 2   | 10   | mA               |
|                                   | $V_{IN} = (V_{OUT} + 5\text{ V})$ , $I_{OUT} = I_{OUT(MAX)}$                    |      | 10  | 20   | mA               |
| Output noise voltage              | 10 Hz to 100 kHz, $I_{OUT} = 5\text{ mA}$                                       |      | 240 |      | $\mu\text{Vrms}$ |
| Long-term stability               | 1000 Hrs.                                                                       |      | 32  |      | mV               |
| Dropout voltage                   | $I_{OUT} = I_{OUT(MAX)}$                                                        |      | 0.5 | 1    | V                |
|                                   | $I_{OUT} = 50\text{ mA}$                                                        |      | 110 | 250  | mV               |
| Short-circuit current             |                                                                                 | 0.6  | 1   |      | A                |
| Peak line transient voltage       | $t_f < 100\text{ ms}$ , $R_L = 100\text{ }\Omega$                               | 60   | 75  |      | V                |
| Maximum operational input voltage |                                                                                 | 26   |     |      | V                |
| Reverse DC input voltage          | $V_{OUT} \geq -0.6\text{ V}$ , $R_L = 100\text{ }\Omega$                        | -15  | -30 |      | V                |
| Reverse transient input voltage   | $t_r < 1\text{ ms}$ , $R_L = 100\text{ }\Omega$                                 | -50  | -75 |      | V                |

## 6.7 Electrical Characteristics: LM2937-10

Unless otherwise specified:  $V_{IN} = V_{OUT(NOM)} + 5\text{ V}$ ;  $I_{OUT(MAX)} = 500\text{ mA}$  for the TO-220 and DDPak/TO-263 packages;  $I_{OUT(MAX)} = 400\text{ mA}$  for the SOT-223 package; and  $C_{OUT} = 10\text{ }\mu\text{F}$ . Conditions and the associated Minimum and Maximum limits apply over the Recommended Operating temperature range for the specific package, unless otherwise noted.

| PARAMETER       | CONDITIONS                                                                      | MIN | TYP | MAX  | UNIT |
|-----------------|---------------------------------------------------------------------------------|-----|-----|------|------|
| Output voltage  | $T_A = T_J = 25^\circ\text{C}$ , $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$   | 9.7 | 10  | 10.3 | V    |
|                 | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                    | 9.5 | 10  | 10.5 | V    |
| Line regulation | $(V_{OUT} + 2\text{ V}) \leq V_{IN} \leq 26\text{ V}$ , $I_{OUT} = 5\text{ mA}$ |     | 30  | 100  | mV   |

**LM2937**

SNVS100F –MARCH 2000–REVISED JULY 2014

[www.ti.com](http://www.ti.com)
**Electrical Characteristics: LM2937-10 (continued)**

Unless otherwise specified:  $V_{IN} = V_{OUT(NOM)} + 5\text{ V}$ ;  $I_{OUT(MAX)} = 500\text{ mA}$  for the TO-220 and DDPAK/TO-263 packages;  $I_{OUT(MAX)} = 400\text{ mA}$  for the SOT-223 package; and  $C_{OUT} = 10\text{ }\mu\text{F}$ . Conditions and the associated Minimum and Maximum limits apply over the Recommended Operating temperature range for the specific package, unless otherwise noted.

| PARAMETER                         | CONDITIONS                                                                      | MIN | TYP | MAX | UNIT             |
|-----------------------------------|---------------------------------------------------------------------------------|-----|-----|-----|------------------|
| Load regulation                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                    |     | 10  | 100 | mV               |
| Quiescent Current                 | $(V_{OUT} + 2\text{ V}) \leq V_{IN} \leq 26\text{ V}$ , $I_{OUT} = 5\text{ mA}$ |     | 2   | 10  | mA               |
|                                   | $V_{IN} = (V_{OUT} + 5\text{ V})$ , $I_{OUT} = I_{OUT(MAX)}$                    |     | 10  | 20  | mA               |
| Output noise voltage              | 10 Hz to 100 kHz, $I_{OUT} = 5\text{ mA}$                                       |     | 300 |     | $\mu\text{Vrms}$ |
| Long-term stability               | 1000 Hrs.                                                                       |     | 40  |     | mV               |
| Dropout voltage                   | $I_{OUT} = I_{OUT(MAX)}$                                                        |     | 0.5 | 1   | V                |
|                                   | $I_{OUT} = 50\text{ mA}$                                                        |     | 110 | 250 | mV               |
| Short-circuit current             |                                                                                 | 0.6 | 1   |     | A                |
| Peak line transient voltage       | $t_f < 100\text{ ms}$ , $R_L = 100\text{ }\Omega$                               | 60  | 75  |     | V                |
| Maximum operational input voltage |                                                                                 | 26  |     |     | V                |
| Reverse DC input voltage          | $V_{OUT} \geq -0.6\text{ V}$ , $R_L = 100\text{ }\Omega$                        | -15 | -30 |     | V                |
| Reverse transient input voltage   | $t_r < 1\text{ ms}$ , $R_L = 100\text{ }\Omega$                                 | -50 | -75 |     | V                |

## 6.8 Electrical Characteristics: LM2937-12

Unless otherwise specified:  $V_{IN} = V_{OUT(NOM)} + 5\text{ V}$ ;  $I_{OUT(MAX)} = 500\text{ mA}$  for the TO-220 and DDPAK/TO-263 packages;  $I_{OUT(MAX)} = 400\text{ mA}$  for the SOT-223 package; and  $C_{OUT} = 10\text{ }\mu\text{F}$ . Conditions and the associated Minimum and Maximum limits apply over the Recommended Operating temperature range for the specific package, unless otherwise noted.







| PARAMETER                         | CONDITIONS                                                                    | MIN   | TYP | MAX   | UNIT             |
|-----------------------------------|-------------------------------------------------------------------------------|-------|-----|-------|------------------|
| Output voltage                    | $T_A = T_J = 25^\circ\text{C}$ , $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$ | 11.64 | 12  | 12.36 | V                |
|                                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                  | 11.4  | 12  | 12.6  | V                |
| Line regulation                   | $(V_{OUT} + 2\text{V}) \leq V_{IN} \leq 26\text{V}$ , $I_{OUT} = 5\text{ mA}$ |       | 36  | 120   | mV               |
| Load regulation                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                  |       | 12  | 120   | mV               |
| Quiescent Current                 | $(V_{OUT} + 2\text{V}) \leq V_{IN} \leq 26\text{V}$ , $I_{OUT} = 5\text{ mA}$ |       | 2   | 10    | mA               |
|                                   | $V_{IN} = (V_{OUT} + 5\text{V})$ , $I_{OUT} = I_{OUT(MAX)}$                   |       | 10  | 20    | mA               |
| Output noise voltage              | 10 Hz to 100 kHz, $I_{OUT} = 5\text{ mA}$                                     |       | 360 |       | $\mu\text{Vrms}$ |
| Long-term stability               | 1000 Hrs.                                                                     |       | 44  |       | mV               |
| Dropout voltage                   | $I_{OUT} = I_{OUT(MAX)}$                                                      |       | 0.5 | 1     | V                |
|                                   | $I_{OUT} = 50\text{ mA}$                                                      |       | 110 | 250   | mV               |
| Short-circuit current             |                                                                               | 0.6   | 1   |       | A                |
| Peak line transient voltage       | $t_f < 100\text{ ms}$ , $R_L = 100\text{ }\Omega$                             | 60    | 75  |       | V                |
| Maximum operational input voltage |                                                                               | 26    |     |       | V                |
| Reverse DC input voltage          | $V_{OUT} \geq -0.6\text{ V}$ , $R_L = 100\text{ }\Omega$                      | -15   | -30 |       | V                |
| Reverse transient input voltage   | $t_r < 1\text{ ms}$ , $R_L = 100\text{ }\Omega$                               | -50   | -75 |       | V                |

## 6.9 Electrical Characteristics: LM2937-15


Unless otherwise specified:  $V_{IN} = V_{OUT(NOM)} + 5\text{ V}$ ;  $I_{OUT(MAX)} = 500\text{ mA}$  for the TO-220 and DDPAK/TO-263 packages;  $I_{OUT(MAX)} = 400\text{ mA}$  for the SOT-223 package; and  $C_{OUT} = 10\text{ }\mu\text{F}$ . Conditions and the associated Minimum and Maximum limits apply over the Recommended Operating temperature range for the specific package, unless otherwise noted.

| PARAMETER                         | CONDITIONS                                                                    | MIN   | TYP | MAX   | UNIT             |
|-----------------------------------|-------------------------------------------------------------------------------|-------|-----|-------|------------------|
| Output voltage                    | $T_A = T_J = 25^\circ\text{C}$ , $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$ | 14.55 | 15  | 15.45 | V                |
|                                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                  | 14.25 | 15  | 15.75 | V                |
| Line regulation                   | $(V_{OUT} + 2\text{V}) \leq V_{IN} \leq 26\text{V}$ , $I_{OUT} = 5\text{ mA}$ |       | 45  | 150   | mV               |
| Load regulation                   | $5\text{ mA} \leq I_{OUT} \leq I_{OUT(MAX)}$                                  |       | 15  | 150   | mV               |
| Quiescent Current                 | $(V_{OUT} + 2\text{V}) \leq V_{IN} \leq 26\text{V}$ , $I_{OUT} = 5\text{ mA}$ |       | 2   | 10    | mA               |
|                                   | $V_{IN} = (V_{OUT} + 5\text{V})$ , $I_{OUT} = I_{OUT(MAX)}$                   |       | 10  | 20    | mA               |
| Output noise voltage              | 10 Hz to 100 kHz, $I_{OUT} = 5\text{ mA}$                                     |       | 450 |       | $\mu\text{Vrms}$ |
| Long-term stability               | 1000 Hrs.                                                                     |       | 56  |       | mV               |
| Dropout voltage                   | $I_{OUT} = I_{OUT(MAX)}$                                                      |       | 0.5 | 1     | V                |
|                                   | $I_{OUT} = 50\text{ mA}$                                                      |       | 110 | 250   | mV               |
| Short-circuit current             |                                                                               | 0.6   | 1   |       | A                |
| Peak line transient voltage       | $t_f < 100\text{ ms}$ , $R_L = 100\text{ }\Omega$                             | 60    | 75  |       | V                |
| Maximum operational input voltage |                                                                               | 26    |     |       | V                |
| Reverse DC input voltage          | $V_{OUT} \geq -0.6\text{ V}$ , $R_L = 100\text{ }\Omega$                      | -15   | -30 |       | V                |
| Reverse transient input voltage   | $t_r < 1\text{ ms}$ , $R_L = 100\text{ }\Omega$                               | -50   | -75 |       | V                |


## 6.10 Typical Characteristics


**Figure 1. Dropout Voltage vs. Output Current**

**Figure 2. Dropout Voltage vs. Temperature**

**Figure 3. Output Voltage vs. Temperature**

**Figure 4. Quiescent Current vs. Temperature**

**Figure 5. Quiescent Current vs. Input Voltage**

**Figure 6. Quiescent Current vs. Output Current**


## Typical Characteristics (continued)




**Figure 7. Line Transient Response**




**Figure 8. Load Transient Response**




**Figure 9. Ripple Rejection**



**Figure 10. Output Impedance**








**Figure 11. Maximum Power Dissipation (TO-220)<sup>1</sup>**



**Figure 12. Maximum Power Dissipation (DDPAK/TO-263)**

1. The maximum allowable power dissipation at any ambient temperature is  $P_{MAX} = (125^{\circ}\text{C} - T_A)/R_{\theta JA}$ , where 125 is the maximum junction temperature for operation,  $T_A$  is the ambient temperature, and  $R_{\theta JA}$  is the junction-to-ambient thermal resistance. If this dissipation is exceeded, the die temperature will rise above 125°C and the electrical specifications do not apply. If the die temperature rises above 150°C, the LM2937 will go into thermal shutdown.


**Typical Characteristics (continued)**

**Figure 13. Low-Voltage Behavior**

**Figure 14. Low-Voltage Behavior**

**Figure 15. Output at Voltage Extremes**

**Figure 16. Output Capacitor ESR**

**Figure 17. Peak Output Current**

## 7 Detailed Description

### 7.1 Overview

The LM2937 is a positive voltage regulator capable of supplying up to 500 mA of load current. The use of a PNP power transistor provides a low dropout voltage characteristic. With a load current of 500 mA the minimum input to output voltage differential required for the output to remain in regulation is typically 0.5 V (1 V ensured maximum over the full operating temperature range). Special circuitry has been incorporated to minimize the quiescent current to typically only 10 mA with a full 500-mA load current when the input to output voltage differential is greater than 3 V.

### 7.2 Functional Block Diagram



### 7.3 Feature Description

#### 7.3.1 Thermal Shutdown (TSD)

The Thermal Shutdown circuitry of the LM2937 has been designed to protect the device against temporary thermal overload conditions. The TSD circuitry is not intended to replace proper heat-sinking. Continuously running the LM2937 device at thermal shutdown may degrade device reliability as the junction temperature will be exceeding the absolute maximum junction temperature rating.

#### 7.3.2 Short Circuit Current Limit

The output current limiting circuitry of the LM2937 has been designed to limit the output current in cases where the load impedance is unusually low. This includes situations where the output may be shorted directly to ground. Continuous operation of the LM2937 at the current limit will typically result in the LM2937 transitioning into Thermal Shutdown mode.

#### 7.3.3 Overvoltage Shutdown (OVSD)

Input voltages greater than typically 32 V will cause the LM2937 output to be disabled. When operating with the input voltage greater than the maximum recommended input voltage of 26 V the device performance is not ensured. Continuous operation with the input voltage greater than the maximum recommended input voltage is discouraged.

## 7.4 Device Functional Modes

The LM2937 design does not include any undervoltage lock-out (UVLO), or enable functions. Generally, the output voltage will track the input voltage until the input voltage is greater than  $V_{OUT} + 1V$ . When the input voltage is greater than  $V_{OUT} + 1V$  the LM2937 will be in linear operation, and the output voltage will be regulated; however, the device will be sensitive to any small perturbation of the input voltage. Device dynamic performance is improved when the input voltage is at least 2 V greater than the output voltage.

## 8 Application and Implementation

### 8.1 Application Information

Figure 18 shows the typical application circuit for the LM2937. The output capacitor,  $C_{OUT}$ , must have a capacitance value of at least 10  $\mu\text{F}$  with an ESR of at least 10 m $\Omega$ , but no more than 3  $\Omega$ . The minimum capacitance value, and the ESR requirements apply across the entire expected operating ambient temperature range.

### 8.2 Typical Application




Figure 18. LM2937 Typical Application

\*Required if the regulator is located more than 3 inches from the power-supply-filter capacitors.

\*\*Required for stability.  $C_{OUT}$  must be at least 10  $\mu\text{F}$  (over full expected operating temperature range) and located as close as possible to the regulator. The equivalent series resistance, ESR, of this capacitor may be as high as 3  $\Omega$ .

#### 8.2.1 Design Requirements

For this design example, use the parameters listed in Table 1:

Table 1. Design Parameters

| DESIGN PARAMETER                   | EXAMPLE VALUE                                                                                                                                                                                                                                                                                                                |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output voltage                     | 8 V                                                                                                                                                                                                                                                                                                                          |
| Input voltage                      | 10 V to 26 V                                                                                                                                                                                                                                                                                                                 |
| Output current requirement         | 5 mA to $I_{OUT(MAX)}$ (see <a href="#">Electrical Characteristics: LM2937-5</a> , <a href="#">Electrical Characteristics: LM2937-8</a> , <a href="#">Electrical Characteristics: LM2937-10</a> , <a href="#">Electrical Characteristics: LM2937-12</a> , <a href="#">Electrical Characteristics: LM2937-15</a> for details) |
| Input capacitor value              | 0.1 $\mu\text{F}$                                                                                                                                                                                                                                                                                                            |
| Output capacitor capacitance value | 10 $\mu\text{F}$ minimum                                                                                                                                                                                                                                                                                                     |
| Output capacitor ESR value         | 0.01 $\Omega$ to 3 $\Omega$                                                                                                                                                                                                                                                                                                  |

#### 8.2.2 Detailed Design Procedure

##### 8.2.2.1 External Capacitors

The output capacitor is critical to maintaining regulator stability, and must meet the required conditions for both Equivalent Series Resistance (ESR) and minimum amount of capacitance.


Minimum Capacitance:

The minimum output capacitance required to maintain stability is 10  $\mu\text{F}$ . (This value may be increased without limit.) Larger values of output capacitance will give improved transient response.

ESR Limits:

The ESR of the output capacitor will cause loop instability if it is too high or too low. The acceptable range of ESR plotted versus load current is shown in the graph below. **It is essential that the output capacitor meet these requirements, or oscillations can result.**

### 8.2.2.2 Output Capacitor ESR



**Figure 19. ESR Limits**

It is important to note that for most capacitors, ESR is specified only at room temperature. However, the designer must ensure that the ESR will stay inside the limits shown over the entire operating temperature range for the design.

For aluminum electrolytic capacitors, ESR will increase by about 30X as the temperature is reduced from 25°C to –40°C. This type of capacitor is not well-suited for low temperature operation.

Solid tantalum capacitors have a more stable ESR over temperature, but are more expensive than aluminum electrolytics. A cost-effective approach sometimes used is to parallel an aluminum electrolytic with a solid Tantalum, with the total capacitance split about 75/25% with the Aluminum being the larger value.


If two capacitors are paralleled, the effective ESR is the parallel of the two individual values. The “flatter” ESR of the Tantalum will keep the effective ESR from rising as quickly at low temperatures.

### 8.2.2.3 Heatsinking

A heatsink may be required depending on the maximum power dissipation and maximum ambient temperature of the application. Under all possible operating conditions, the junction temperature must be within the range specified under [Absolute Maximum Ratings](#).

To determine if a heatsink is required, the power dissipated by the regulator,  $P_D$ , must be calculated.

[Figure 20](#) below shows the voltages and currents which are present in the circuit, as well as the formula for calculating the power dissipated in the regulator:



**Figure 20. Power Dissipation Diagram**

The next parameter which must be calculated is the maximum allowable temperature rise,  $T_R$  (max). This is calculated by using the formula:

$$T_R \text{ (max)} = T_J \text{ (max)} - T_A \text{ (max)}$$

where

- $T_J$  (max) is the maximum allowable junction temperature, which is 125°C for the TO-220 and TO-263 packages, and 85°C for the SOT-223 package.
- $T_A$  (max) is the maximum ambient temperature which will be encountered in the application. (1)

Using the calculated values for  $T_R$ (max) and  $P_D$ , the maximum allowable value for the junction-to-ambient thermal resistance,  $R_{\theta JA}$ , can now be found:

$$R_{\theta JA} = T_R (\text{max})/P_D \quad (2)$$

#### NOTE

**IMPORTANT:** If the maximum allowable value for  $R_{\theta JA}$  is found to be  $\geq 53^\circ\text{C/W}$  for the TO-220 package,  $\geq 80^\circ\text{C/W}$  for the DDPAK/TO-263 package, or  $\geq 174^\circ\text{C/W}$  for the SOT-223 package, no heatsink is needed since the package alone will dissipate enough heat to satisfy these requirements.

If the calculated value for  $R_{\theta JA}$  falls below these limits, a heatsink is required.

#### 8.2.2.4 Heatsinking TO-220 Package Parts

The TO-220 can be attached to a typical heatsink, or secured to a copper plane on a PC board. If a copper plane is to be used, the values of  $R_{\theta JA}$  will be the same as shown in the next section for the DDPAK/TO-263.

If a manufactured heatsink is to be selected, the value of heatsink-to-ambient thermal resistance,  $R_{\theta HA}$ , must first be calculated:

$$R_{\theta HA} = R_{\theta JA} - R_{\theta JC} - R_{\theta CH}$$

where

- $R_{\theta JC}$  is defined as the thermal resistance from the junction to the surface of the case. A value of  $3^\circ\text{C/W}$  can be assumed for  $R_{\theta JC}$  for this calculation
- $R_{\theta CH}$  is defined as the thermal resistance between the case and the surface of the heatsink. The value of  $R_{\theta CH}$  will vary from about  $1.5^\circ\text{C/W}$  to about  $2.5^\circ\text{C/W}$  (depending on method of attachment, insulator, etc.). If the exact value is unknown,  $2^\circ\text{C/W}$  should be assumed for  $R_{\theta CH}$  (3)


When a value for  $R_{\theta HA}$  is found using the equation shown, *a heatsink must be selected that has a value that is less than or equal to this number.*

$R_{\theta HA}$  is specified numerically by the heatsink manufacturer in the catalog, or shown in a curve that plots temperature rise vs power dissipation for the heatsink.

#### 8.2.2.5 Heatsinking DDPAK/TO-263 and SOT-223 Package Parts

Both the DDPAK/TO-263 and SOT-223 packages use a copper plane on the PCB and the PCB itself as a heatsink. To optimize the heat sinking ability of the plane and PCB, solder the tab of the package to the plane.


Figure 21 shows for the DDPAK/TO-263 the measured values of  $R_{\theta JA}$  for different copper area sizes using a typical PCB with 1 ounce copper and no solder mask over the copper area used for heatsinking.



**Figure 21.  $R_{\theta JA}$  vs. Copper (1 ounce) Area for the DDPAK/TO-263 Package**


As shown in [Figure 21](#), increasing the copper area beyond 1 square inch produces very little improvement. It should also be observed that the minimum value of  $R_{\theta JA}$  for the DDPAK/TO-263 package mounted to a PCB is 32°C/W.

As a design aid, [Figure 22](#) shows the maximum allowable power dissipation compared to ambient temperature for the DDPAK/TO-263 device (assuming  $R_{\theta JA}$  is 35°C/W and the maximum junction temperature is 125°C).




**Figure 22. Maximum Power Dissipation vs.  $T_{AMB}$  for the DDPAK/TO-263 Package**

[Figure 23](#) and [Figure 24](#) show information for the SOT-223 package. [Figure 24](#) assumes an  $R_{\theta JA}$  of 74°C/W for 1 ounce copper and 51°C/W for 2 ounce copper and a maximum junction temperature of 85°C.



**Figure 23.  $R_{\theta JA}$  vs Copper (2 ounce) Area for the SOT-223 Package**




**Figure 24. Maximum Power Dissipation vs  $T_{AMB}$  for the SOT-223 Package**

### 8.2.2.6 SOT-223 Soldering Recommendations


It is not recommended to use hand soldering or wave soldering to attach the small SOT-223 package to a printed circuit board. The excessive temperatures involved may cause package cracking.

Either vapor phase or infrared reflow techniques are preferred soldering attachment methods for the SOT-223 package.

### 8.2.3 Application Curves



**Figure 25. Output at Voltage Extremes**



**Figure 26. Dropout Voltage vs. Temperature**

## 9 Power Supply Recommendations

This device is designed to operate from an input supply voltage from at least  $V_{OUT} + 1$  V up to a maximum of 26 V. The input supply should be well regulated and free of spurious noise. To ensure that the LM2937 output voltage is well regulated the input supply should be at least  $V_{OUT} + 2$  V. A capacitor at the INPUT pin may not be specifically required if the bulk input supply filter capacitors are within three inches of the INPUT pin, but adding one will not be detrimental to operation.


## 10 Layout

### 10.1 Layout Guidelines

The dynamic performance of the LM2937 is dependent on the layout of the PCB. PCB layout practices that are adequate for typical LDO's may degrade the PSRR, noise, or transient performance of the LM2937. Best performance is achieved by placing  $C_{IN}$  and  $C_{OUT}$  on the same side of the PCB as the LM2937, and as close as is practical to the package. The ground connections for  $C_{IN}$  and  $C_{OUT}$  should be back to the LM2937 ground pin using as wide, and as short, of a copper trace as is practical.

Connections using long trace lengths, narrow trace widths, and/or connections through vias should be avoided as these will add parasitic inductances and resistances that will give inferior performance, especially during transient conditions

### 10.2 Layout Example



**Figure 27. LM2937 SOT-223-4 Layout**

## 11 Device and Documentation Support

### 11.1 Trademarks

All trademarks are the property of their respective owners.

### 11.2 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

### 11.3 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 12 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

**PACKAGING INFORMATION**

| Orderable Device   | Status<br>(1) | Package Type     | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|--------------------|---------------|------------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| LM2937ES-10        | LIFEBUY       | DDPAK/<br>TO-263 | KTT                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ES<br>-10         |                         |
| LM2937ES-10/NOPB   | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 45             | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-10         | <a href="#">Samples</a> |
| LM2937ES-12        | NRND          | DDPAK/<br>TO-263 | KTT                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ES<br>-12         |                         |
| LM2937ES-12/NOPB   | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 45             | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-12         | <a href="#">Samples</a> |
| LM2937ES-15        | NRND          | DDPAK/<br>TO-263 | KTT                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ES<br>-15         |                         |
| LM2937ES-15/NOPB   | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 45             | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-15         | <a href="#">Samples</a> |
| LM2937ES-5.0       | NRND          | DDPAK/<br>TO-263 | KTT                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ES<br>-5.0        |                         |
| LM2937ES-5.0/NOPB  | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 45             | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-5.0        | <a href="#">Samples</a> |
| LM2937ES-8.0/NOPB  | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 45             | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-8.0        | <a href="#">Samples</a> |
| LM2937ESX-12/NOPB  | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 500            | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-12         | <a href="#">Samples</a> |
| LM2937ESX-15/NOPB  | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 500            | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-15         | <a href="#">Samples</a> |
| LM2937ESX-5.0      | NRND          | DDPAK/<br>TO-263 | KTT                | 3    | 500            | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ES<br>-5.0        |                         |
| LM2937ESX-5.0/NOPB | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 500            | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-5.0        | <a href="#">Samples</a> |
| LM2937ESX-8.0/NOPB | ACTIVE        | DDPAK/<br>TO-263 | KTT                | 3    | 500            | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-3-245C-168 HR  | -40 to 125   | LM2937ES<br>-8.0        | <a href="#">Samples</a> |
| LM2937ET-10/NOPB   | ACTIVE        | TO-220           | NDE                | 3    | 45             | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-NA-UNLIM     | -40 to 125   | LM2937ET<br>-10         | <a href="#">Samples</a> |
| LM2937ET-12        | NRND          | TO-220           | NDE                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ET<br>-12         |                         |
| LM2937ET-12/NOPB   | ACTIVE        | TO-220           | NDE                | 3    | 45             | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-NA-UNLIM     | -40 to 125   | LM2937ET<br>-12         | <a href="#">Samples</a> |

| Orderable Device    | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|---------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| LM2937ET-15         | NRND          | TO-220       | NDE                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ET<br>-15         |                         |
| LM2937ET-15/NOPB    | ACTIVE        | TO-220       | NDE                | 3    | 45             | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-NA-UNLIM     | -40 to 125   | LM2937ET<br>-15         | <a href="#">Samples</a> |
| LM2937ET-5.0        | NRND          | TO-220       | NDE                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ET<br>-5.0        |                         |
| LM2937ET-5.0/NOPB   | ACTIVE        | TO-220       | NDE                | 3    | 45             | Pb-Free (RoHS<br>Exempt)   | CU SN                   | Level-1-NA-UNLIM     | -40 to 125   | LM2937ET<br>-5.0        | <a href="#">Samples</a> |
| LM2937ET-8.0        | NRND          | TO-220       | NDE                | 3    | 45             | TBD                        | Call TI                 | Call TI              | -40 to 125   | LM2937ET<br>-8.0        |                         |
| LM2937ET-8.0/NOPB   | ACTIVE        | TO-220       | NDE                | 3    | 45             | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-NA-UNLIM     | -40 to 125   | LM2937ET<br>-8.0        | <a href="#">Samples</a> |
| LM2937IMP-10        | NRND          | SOT-223      | DCY                | 4    | 1000           | TBD                        | Call TI                 | Call TI              | -40 to 85    | L73B                    |                         |
| LM2937IMP-10/NOPB   | ACTIVE        | SOT-223      | DCY                | 4    | 1000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L73B                    | <a href="#">Samples</a> |
| LM2937IMP-12        | NRND          | SOT-223      | DCY                | 4    | 1000           | TBD                        | Call TI                 | Call TI              | -40 to 85    | L74B                    |                         |
| LM2937IMP-12/NOPB   | ACTIVE        | SOT-223      | DCY                | 4    | 1000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L74B                    | <a href="#">Samples</a> |
| LM2937IMP-5.0       | NRND          | SOT-223      | DCY                | 4    | 1000           | TBD                        | Call TI                 | Call TI              | -40 to 85    | L71B                    |                         |
| LM2937IMP-5.0/NOPB  | ACTIVE        | SOT-223      | DCY                | 4    | 1000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L71B                    | <a href="#">Samples</a> |
| LM2937IMP-8.0/NOPB  | ACTIVE        | SOT-223      | DCY                | 4    | 1000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L72B                    | <a href="#">Samples</a> |
| LM2937IMPX-10/NOPB  | ACTIVE        | SOT-223      | DCY                | 4    | 2000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L73B                    | <a href="#">Samples</a> |
| LM2937IMPX-12/NOPB  | ACTIVE        | SOT-223      | DCY                | 4    | 2000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L74B                    | <a href="#">Samples</a> |
| LM2937IMPX-15/NOPB  | ACTIVE        | SOT-223      | DCY                | 4    | 2000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L75B                    | <a href="#">Samples</a> |
| LM2937IMPX-5.0/NOPB | ACTIVE        | SOT-223      | DCY                | 4    | 2000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L71B                    | <a href="#">Samples</a> |
| LM2937IMPX-8.0      | NRND          | SOT-223      | DCY                | 4    | 2000           | TBD                        | Call TI                 | Call TI              | -40 to 85    | L72B                    |                         |
| LM2937IMPX-8.0/NOPB | ACTIVE        | SOT-223      | DCY                | 4    | 2000           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | L72B                    | <a href="#">Samples</a> |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device             | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|--------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LM2937ESX-12/NOPB  | DDPAK/TO-263 | KTT             | 3    | 500  | 330.0              | 24.4               | 10.75   | 14.85   | 5.0     | 16.0    | 24.0   | Q2            |
| LM2937ESX-15/NOPB  | DDPAK/TO-263 | KTT             | 3    | 500  | 330.0              | 24.4               | 10.75   | 14.85   | 5.0     | 16.0    | 24.0   | Q2            |
| LM2937ESX-5.0      | DDPAK/TO-263 | KTT             | 3    | 500  | 330.0              | 24.4               | 10.75   | 14.85   | 5.0     | 16.0    | 24.0   | Q2            |
| LM2937ESX-5.0/NOPB | DDPAK/TO-263 | KTT             | 3    | 500  | 330.0              | 24.4               | 10.75   | 14.85   | 5.0     | 16.0    | 24.0   | Q2            |
| LM2937ESX-8.0/NOPB | DDPAK/TO-263 | KTT             | 3    | 500  | 330.0              | 24.4               | 10.75   | 14.85   | 5.0     | 16.0    | 24.0   | Q2            |
| LM2937IMP-10       | SOT-223      | DCY             | 4    | 1000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMP-10/NOPB  | SOT-223      | DCY             | 4    | 1000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMP-12       | SOT-223      | DCY             | 4    | 1000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMP-12/NOPB  | SOT-223      | DCY             | 4    | 1000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMP-5.0      | SOT-223      | DCY             | 4    | 1000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMP-5.0/NOPB | SOT-223      | DCY             | 4    | 1000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMP-8.0/NOPB | SOT-223      | DCY             | 4    | 1000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMPX-10/NOPB | SOT-223      | DCY             | 4    | 2000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMPX-12/NOPB | SOT-223      | DCY             | 4    | 2000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |

| Device              | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LM2937IMPX-15/NOPB  | SOT-223      | DCY             | 4    | 2000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMPX-5.0/NOPB | SOT-223      | DCY             | 4    | 2000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMPX-8.0      | SOT-223      | DCY             | 4    | 2000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |
| LM2937IMPX-8.0/NOPB | SOT-223      | DCY             | 4    | 2000 | 330.0              | 16.4               | 7.0     | 7.5     | 2.2     | 12.0    | 16.0   | Q3            |

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

| Device             | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|--------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LM2937ESX-12/NOPB  | DDPAK/TO-263 | KTT             | 3    | 500  | 367.0       | 367.0      | 45.0        |
| LM2937ESX-15/NOPB  | DDPAK/TO-263 | KTT             | 3    | 500  | 367.0       | 367.0      | 45.0        |
| LM2937ESX-5.0      | DDPAK/TO-263 | KTT             | 3    | 500  | 367.0       | 367.0      | 45.0        |
| LM2937ESX-5.0/NOPB | DDPAK/TO-263 | KTT             | 3    | 500  | 367.0       | 367.0      | 45.0        |
| LM2937ESX-8.0/NOPB | DDPAK/TO-263 | KTT             | 3    | 500  | 367.0       | 367.0      | 45.0        |
| LM2937IMP-10       | SOT-223      | DCY             | 4    | 1000 | 367.0       | 367.0      | 35.0        |
| LM2937IMP-10/NOPB  | SOT-223      | DCY             | 4    | 1000 | 367.0       | 367.0      | 35.0        |
| LM2937IMP-12       | SOT-223      | DCY             | 4    | 1000 | 367.0       | 367.0      | 35.0        |
| LM2937IMP-12/NOPB  | SOT-223      | DCY             | 4    | 1000 | 367.0       | 367.0      | 35.0        |
| LM2937IMP-5.0      | SOT-223      | DCY             | 4    | 1000 | 367.0       | 367.0      | 35.0        |
| LM2937IMP-5.0/NOPB | SOT-223      | DCY             | 4    | 1000 | 367.0       | 367.0      | 35.0        |
| LM2937IMP-8.0/NOPB | SOT-223      | DCY             | 4    | 1000 | 367.0       | 367.0      | 35.0        |
| LM2937IMPX-10/NOPB | SOT-223      | DCY             | 4    | 2000 | 367.0       | 367.0      | 35.0        |


---

| Device              | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LM2937IMPX-12/NOPB  | SOT-223      | DCY             | 4    | 2000 | 367.0       | 367.0      | 35.0        |
| LM2937IMPX-15/NOPB  | SOT-223      | DCY             | 4    | 2000 | 367.0       | 367.0      | 35.0        |
| LM2937IMPX-5.0/NOPB | SOT-223      | DCY             | 4    | 2000 | 367.0       | 367.0      | 35.0        |
| LM2937IMPX-8.0      | SOT-223      | DCY             | 4    | 2000 | 367.0       | 367.0      | 35.0        |
| LM2937IMPX-8.0/NOPB | SOT-223      | DCY             | 4    | 2000 | 367.0       | 367.0      | 35.0        |

NDE0003B




## PLASTIC SMALL-OUTLINE



DCY (R-PDSO-G4)

PLASTIC SMALL OUTLINE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil recommendations. Refer to IPC 7525 for stencil design considerations.



## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

### Products

|                              |                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------|
| Audio                        | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers                   | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters              | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products                | <a href="http://www.dlp.com">www.dlp.com</a>                                         |
| DSP                          | <a href="http://dsp.ti.com">dsp.ti.com</a>                                           |
| Clocks and Timers            | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface                    | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                        | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt                   | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers             | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                         | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Applications Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity        | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

### TI E2E Community

[e2e.ti.com](http://e2e.ti.com)