

Designated client product

This product will be discontinued its production in the near term.
And it is provided for customers currently in use only, with a time limit.
It can not be available for your new project. Please select other new or existing products.

For more information, please contact our sales office in your region.

New Japan Radio Co.,Ltd.


www.njr.com

VOLTAGE COMPARATOR


■ GENERAL DESCRIPTION

The NJM319 is precision high-speed dual comparator fabricated on a single monolithic chip. It is designed to operate over a wide range of supply voltages down to single 5V logic and ground. The uncommitted collector of the output stage makes the NJM319 compatible with RTL, DTL and TTL as well as capable of driving lamps and relays at currents up to 25mA.

■ PACKAGE OUTLINE



NJM319D



NJM319M




NJM319V

■ FEATURES

- Operating Voltage +5V ~ +18V (Single Supply)
 ±5V ~ ±18V (Dual Supply)
- Single Supply Operation
- Response Time 80ns typ.
- Output Current 25mA @ Sink Current
- Package Outline DIP14, DMP14, SSOP14
- Bipolar Technology


■ PIN CONFIGURATION



PIN FUNCTION

1. NC	8. B GND
2. NC	9. B +INPUT
3. A GND	10. B -INPUT
4. A +INPUT	11. V ⁺
5. A -INPUT	12. A OUTPUT
6. V ⁻	13. NC
7. B OUTPUT	14. NC

■ EQUIVALENT CIRCUIT (1/2 Shown)




■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V^+ / V^-	± 18	V
Input Voltage	V_{IC}	± 15 (note1)	V
Differential Input Voltage	V_{ID}	± 5 (note2)	V
Power Dissipation	P_D	(DIP14) 500 (DMP14, SSOP14) 300	mW
Output to Negative Supply Voltage	ΔV_{O-N}	36	V
Output to GND	ΔV_{O-G}	36	V
GND to Negative Supply Voltage	ΔV_{G-N}	25	V
GND to Positive Supply Voltage	ΔV_{G-P}	18	V
Operating Temperature Range	T_{opr}	-40 to +85	°C
Storage Temperature Range	T_{stg}	-40 to +125	°C

(note1) For supply voltage less than $\pm 15V$, the absolute maximum input voltage is equal to the supply voltage.

(note2) Do not apply voltage more than $\pm 5V$ at the point between +INPUT and -INPUT.



■ RECOMMENDED OPERATING VOLTAGE ($T_a=25^\circ\text{C}$)


PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Dual Supply	V^+	GND=0V	+5	-	+18	V
	V^-		-18	-	0	
Single Supply	V^+	GND = V^-	+5	-	+18	V
GND to Positive Supply Voltage	V_{G-P}	This Voltage is with respect to the GND terminal.	+5	-	+18	V

■ ELECTRICAL CHARACTERISTICS


($T_a=25^{\circ}\text{C}$, $V^+/V^-=\pm 15\text{V}$)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Offset Voltage	V_{IO}	$R_S \leq 5\text{k}\Omega$	-	2.0	8.0	mV
Input Offset Current	I_{IO}		-	80	200	nA
Input Bias Current	I_B		-	250	1000	nA
Voltage Gain	A_V		78	92	-	dB
Input Voltage Range	V_{ICM}	$V^+=15\text{V}, V^-=-15\text{V}$	-	- 13 to 13	-	V
		$V^+=5\text{V}, V^-=0\text{V}$	-	1 to 3	-	V
Response Time	t_R	V_{IN}^+ : 100mV Step Input , 5mV Over Drive	-	80	-	ns
Saturation Voltage	V_{SAT}	$V_{IN}^+ \leq -10\text{mV}, I_{SINK}=25\text{mA}$	-	0.75	1.5	V
Output Leakage Current	I_{LEAK}	$V_{IN}^+ \geq 10\text{mV}, V^-=\text{GND}=0\text{V}, V_{OUT}=35\text{V}$	-	0.2	10	μA
Positive Supply Current	I^+_1	$V^+=5\text{V}, V^-=0\text{V}$	-	4.3	-	mA
Positive Supply Current	I^+_2		-	8	12.5	mA
Negative Supply Current	I^-		-	3	5	mA

■ TYPICAL APPLICATION









Single Supply







Dual Supply

■ TYPICAL CHARACTERISTICS




■ TYPICAL CHARACTERISTICS




■ TYPICAL APPLICATIONS

Relay Driver



Window Detector



[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.