


QUAD DIFFERENTIAL COMPARATOR

The LM239 series consists of four independent voltage comparators designed to operate from single power supply over a wide voltage range.


FEATURES

- Single or dual supply operation
- Wide range of supply voltage
LM239/A, LM339/A, LM2901: 2 ~ 36V (or $\pm 1 \sim \pm 18V$)
LM3302: 2 ~ 28V (or $\pm 1 \sim \pm 14V$)
- Low supply current drain 800 μA Typ
- Open collector outputs for wired and connectors
- Low input bias current 25nA Typ
- Low Input offset current $\pm 2.3nA$ Typ.
- Low input offset voltage $\pm 1.4mV$ Typ.
- Common mode input voltage range includes ground.
- Low output saturation voltage
- Output compatible with TTL, DTL and MOS logic system


BLOCK DIAGRAM



14 DIP




14 SOP



ORDERING INFORMATION

Device	Package	Operating Temperature
LM339N LM339AN	14 DIP	0 ~ +70°C
LM339M LM339AM	14 SOP	
LM239N LM239AN	14 DIP	-25 ~ +85°C
LM239M LM239AM	14 SOP	
LM2901N LM2901M	14 DIP 14 SOP	-40 ~ +85°C
LM3302N LM3302M	14 DIP 14 SOP	

SCHEMATIC DIAGRAM



ABSOLUTE MAXIMUM RATINGS

Characteristic	Symbol	Value	Unit
Supply Voltage	V_{CC}	± 18 or 36	V
Supply Voltage Only LM3302	V_{CC}	± 14 or 28	V
Differential Input Voltage	$V_{I(DIFF)}$	36	V
Differential Input Voltage Only LM3302	$V_{I(DIFF)}$	28	V
Input Voltage	V_I	- 0.3 to +36	V
Input Voltage Only LM3302	V_I	- 0.3 to +28	V
Output Short Circuit to GND		Continuous	
Power Dissipation	P_D	570	mW
Operating Temperature LM339/LM339A	T_{OPR}	0 ~ + 70	°C
LM239/LM239A		- 25 ~ + 85	°C
LM2901/LM3302		- 40 ~ + 85	°C
Storage Temperature	T_{STG}	- 65 ~ + 150	°C

ELECTRICAL CHARACTERISTICS(V_{CC} = 5V, T_A = 25°C, unless otherwise specified)

Characteristic	Symbol	Test Conditions	LM239A/LM339A			LM239/LM339			Unit
			Min	Typ	Max	Min	Typ	Max	
Input Offset Voltage	V _{IO}	V _{CM} = 0V to V _{CC} = 1.5V V _{O(P)} = 1.4V, R _S = 0Ω		±1	±2		±1.4	±5	mV
		NOTE 1			±4.0			±9.0	
Input Offset Current	I _{IO}			±2.3	±50		±2.3	±50	nA
		NOTE 1			±150			±150	
Input Bias Current	I _{BIAS}			57	250		57	250	nA
		NOTE 1			400			400	
Input Common Mode Voltage Range	V _{I(R)}		0		V _{CC} -1.5	0		V _{CC} -1.5	V
		NOTE 1	0		V _{CC} -2	0		V _{CC} -2	
Supply Current	I _{CC}	R _L = ∞		1.1	2.0		1.1	2.0	mA
Voltage Gain	G _V	V _{CC} = 15V, R _L ≥ 15KΩ (for large swing)	50	200		50	200		V/mV
Large Signal Response Time	t _{RES}	V _I = TTL Logic Swing V _{REF} = 1.4V, V _{RL} = 5V, R _L = 5.1KΩ		350			350		ns
Response Time	t _{RES}	V _{RL} = 5V, R _L = 5.1KΩ		1.4			1.4		μs
Output Sink Current	I _{SINK}	V _{I(-)} ≥ 1V, V _{I(+)} = 0V, V _{O(P)} ≤ 1.5V	6	18		6	18		mA
Output Saturation Voltage	V _{SAT}	V _{I(-)} ≥ 1V, V _{I(+)} = 0V I _{SINK} = 4mA		140	400		140	400	mV
		NOTE 1			700			700	
Output Leakage Current	I _{O(LKG)}	V _{I(-)} = 0V V _{I(+)} = 1V		0.1			0.1		nA
		V _{O(P)} = 30V			1.0			1.0	μA
Differential Voltage	V _{I(DIFF)}	NOTE 1			36			36	V

Note 1.

LM339/A: 0 ≤ T_A ≤ +70°CLM239/A: -25 ≤ T_A ≤ +85°CLM2901/3302: -40 ≤ T_A ≤ +85°C

ELECTRICAL CHARACTERISTICS(V_{CC} = 5V, T_A = 25°C, unless otherwise specified)

Characteristic	Symbol	Test Conditions	LM2901			LM3302			Unit
			Min	Typ	Max	Min	Typ	Max	
Input Offset Voltage	V _{IO}	V _{CM} = 0V to V _{CC} = 1.5V		2	7		2	20	mV
		V _{O(P)} = 1.4V, R _S = 0Ω		9	15			40	
Input Offset Current	I _{IO}			2.3	50		3	100	nA
		NOTE 1		50	200			300	
Input Bias Current	I _{BIAS}			57	250		57	250	nA
		NOTE 1		200	500			1000	
Input Common Mode Voltage Range	V _{I(R)}		0		V _{CC} -1.5	0		V _{CC} -1.5	V
		NOTE 1	0		V _{CC} -2	0		V _{CC} -2	
Supply Current	I _{CC}	R _L = ∞		1.1	2.0		1.1	2.0	mA
		R _L = ∞, V _{CC} = 30V		1.6	2.5				
Voltage Gain	G _V	V _{CC} = 15V, R _L ≥ 15KΩ (for large swing)	25	100		2	30		V/mV
Large Signal Response Time	t _{RES}	V _I = TTL Logic Swing V _{REF} = 1.4V, V _{RL} = 5V, R _L = 5.1KΩ		350			350		ns
Response Time	t _{RES}	V _{RL} = 5V, R _L = 5.1KΩ		1.4			1.4		μs
Output Sink Current	I _{SINK}	V _{I(-)} ≥ 1V, V _{I(+)} = 0V, V _{O(P)} ≤ 1.5V	6	18		6	18		mA
Output Saturation Voltage	V _{SAT}	V _{I(-)} ≥ 1V, V _{I(+)} = 0V		140	400		140	400	mV
		I _{SINK} = 4mA			700			700	
Output Leakage Current	I _{O(LKG)}	V _{I(-)} = 0V		0.1			0.1		nA
		V _{I(+)} = 1V			1.0			1.0	
Differential Voltage	V _{I(DIFF)}	NOTE 1			36			36	V

Note 1.

LM339/A: 0 ≤ T_A ≤ +70°CLM239/A: -25 ≤ T_A ≤ +85°CLM2901/3302: -40 ≤ T_A ≤ +85°C

TYPICAL PERFORMANCE CHARACTERISTICS

Fig. 1 SUPPLY CURRENT




Fig. 2 INPUT CURRENT




Fig. 3 OUTPUT SATURATION VOLTAGE




Fig. 4 RESPONSE TIME FOR VARIOUS INPUT OVERDRIVE-NEGATIVE TRANSITION





Fig. 5 RESPONSE TIME FOR VARIOUS INPUT OVERDRIVE-POSITIVE TRANSITION



TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE ^x	ISOPLANAR TM
CoolFET TM	MICROWIRE TM
CROSSVOLT TM	POP TM
E ² CMOS TM	PowerTrench TM
FACT TM	QS TM
FACT Quiet Series TM	Quiet Series TM
FAST [®]	SuperSOT TM -3
FAST ^r	SuperSOT TM -6
GTO TM	SuperSOT TM -8
HiSeC TM	TinyLogic TM

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.