



N Male
F4PNMV2-H



N Female Bulkhead
F4PNF-BH



UHF Male
44ASP



N Male Right Angle
F4PNR-H



7/8" EIA
44ASR



7-16 DIN Female
F4PDF-C



7-16 DIN Male
F4PDMV2-C

Connectors

Interface	Description	Type Number	Inner Contact Attachment	Outer Contact Attachment	Plating Code	Max. Length in (mm)	Max. Dia. in (mm)
N Male	Hex Head	F4PNMV2-H	Solder	Crush-Flare	SG	2.13 (54.0)	0.94 (23.8)
N Male	Hex Head	F4PNMV2-HC	Captivated	Crush-Flare	SG	2.13 (54.0)	0.94 (23.8)
N Male	Rt Angle, Hex Hd	F4PNR-H	Solder	Tab-Flare	SG	3.3/1.5 (84/38)	0.86 (21.8)
N Male		F4PNR-HC	Captivated	Crush-Flare	SG	2.8 (71.9)/1.6 (41.5)	1 (25.7)
N Female	—	F4PNF	Solder	Self-Flare	SG	2.3 (53.3)	0.88 (22.4)
N Female	—	F4PNF-C	Captivated	Self-Flare	SG	2.3 (53.3)	0.88 (22.4)
N Female	Bulkhead	F4PNF-BH	Solder	Self-Flare	SG	2.3 (58)	0.95 (24.1)
4.1/9.5 DIN Male	—	F4PKM-C	Captivated	Self-Flare	SS	2.0 (50)	0.95 (24.1)
4.1/9.5 DIN Male	Rt Angle, Outdoor Use	F4PKR-C	Captivated	Self-Flare	SS	2.3/1.5 (57/38)	0.95 (24.1)
7-16 DIN Male	—	F4PDMV2-C	Captivated	Crush-Flare	SS	1.98 (50.2)	1.05 (26.7)
7-16 DIN Male	—	F4PDMV2	Solder	Crush-Flare	SS	2.10 (53.4)	1.05 (26.7)
7-16 DIN Male	Right Angle	F4PDR	Solder	Self-Flare	SS	2.4/1.8 (61/46)	1.4 (35.6)
7-16 DIN Male	Right Angle	F4PDR-C	Captivated	Self-Flare	SS	2.1/2.0 (53/50)	1.4 (35.6)
7-16 DIN Female	—	F4PDF-C	Captivated	Self-Flare	SS	2.0 (50)	1.1 (27.9)
7-16 DIN Female	—	F4PDF	Solder	Self-Flare	SS	2.0 (50)	1.1 (27.9)
7-16 DIN Female	Bulkhead	F4PDF-BH	Solder	Self-Flare	SS	2.01 (51.1)	1.50 (38)
7-16 DIN Female	Panel Mount	F4PDF-PM	Solder	Self-Flare	SS	2.01 (51.1)	1.26 (32)
7-16 DIN Female	Bulkhead	F4PDF-BHC	Captivated	Self-Flare	SS	2.0 (50)	1.8 (45.7)
7-16 DIN Female	Panel Mount	F4PDF-PMC	Captivated	Self-Flare	SS	2.0 (50)	1.3 (33)
7/8" EIA Flange	—	44ASR	Solder	Tab-Flare	BS	3.3 (84)	1.4 (35.6)
UHF Male	—	44ASP	Solder	Tab-Flare	BS	2.1 (53)	0.84 (21.3)
UHF Female	—	44ASU	Solder	Tab-Flare	BS	2.3 (58)	0.84 (21.3)
HN Male	—	44ASJ	Solder	Tab-Flare	BB	2.4 (61)	0.84 (21.3)
SC Male	—	44SPCW	Solder	Tab-Flare	SG	2.7 (69)	0.88 (22.4)

Plating Codes: BB - Brass Body and Pin, BS - Brass Body and Silver Plated Pin, SG - Silver Plated Body and Gold Plated Pin, SS - Silver Plated Body and Pin

Connector Accessories – See page 624

Factory Attached Connectors – For factory made cable assemblies and jumper cables, see pages 584-587.